



Constant Flow Monitor Nozzles

Features

- Constructed of Corrosion Resistant Brass
- 2-1/2" FNST Inlet
- 100 PSI Flow Rate
- (6) Different Sizes Available
- Flow Remains Constant In All Patterns
- Grease Fittings For Easy Maintenance
- Combination of Fog and Straight Stream
- Built-In Grid as Stream Shaper for Maximum Reach
- Heavy Duty Protective Bumper(1000 GPM Only)



Suitable

- Excellent for Industrial, Marine and Offshore use
- Suitable for use with water or AFFF Solution

Chemguard CMNB Monitor Nozzles Range Data - Reach in Feet**						
Part No:	Discharge Pattern	Reach in Feet @ Following Pessures				
		40	60	80	100	125
CMNB-300	Stream	105	125	140	144	150
	Narrow Fog	74	95	105	112	120
	Wide Fog	48	56	60	67	74
CMNB-350	Stream	107	127	142	146	152
	Narrow Fog	75	96	106	113	122
	Wide Fog	48	57	61	68	75
CMNB-500	Stream	118	140	156	170	186
	Narrow Fog	80	100	110	115	124
	Wide Fog	49	58	65	71	78
CMNB-700	Stream	138	175	198	215	240
	Narrow Fog	92	110	128	150	160
	Wide Fog	44	50	55	60	66
CMNB-750	Stream	130	170	190	205	235
	Narrow Fog	90	105	125	145	155
	Wide Fog	42	49	54	60	65
CMNB-1000	Stream	160	205	242	255	280
	Narrow Fog	80	98	118	155	168
	Wide Fog	55	73	88	95	110

* Maximum reach on stream is achieved at approximately 30-35 degrees elevation.

** Some ranges based on exterpolation of existing data and observations.

CHEM GUARD
204 S. 6th Ave • Mansfield, Tx 76063 • (817) 473-9964 • FAX (817) 473-0606

www.chemguard.com