



Figure No. 4405

CARBON DIOXIDE CO2 Fire Extinguishers * Series 4400

U/L LISTED

STANDARD EQUIPMENT:

The industry's first high pressure, seamless, lightweight heavy duty aluminum cylinder. 4400 Series extinguishers, are absolutely rust free and 30% lighter in weight.

IDEAL USES:

Chemical and manufacturing plant and oil rigs. Rail yards, warehouses, construction sites, mechanical equipment rooms and large laboratories.





Figure No. 4410

Figure No.	U/L Rating	Capacity (lbs.)	Height	Width	Depth (dia.)	Range of Sream	Valve Material	Cylinder Material	Coast Guard Approved	Bracket	Shipping Weight (Ibs.)
4405	5B:C	5	17 3/8"	8 1/4"	5 1/4"	4-8'	Brass	Alum.	Yes	Wall	13 3/4Lbs.
4410	10B:C	10	19 3/4"	12"	6 15/16"	4-8'	Brass	Alum.	Yes	Wall	27 3/4Lbs.
4415	10B:C	15	26 3/8"	12"	6 7/8"	4-8'	Brass	Alum.	Yes	Wall	37 3/4Lbs.
4420	10B:C	20	26 7/8"	13"	8"	4-8'	Brass	Alum.	Yes	Wall	49 Lbs.





STORED PRESSURE*Series 4400

Additional protection suitable for many local applications. Vertical mounting with optional horizontal and upright versions available. Designed for individual hazard protection.

NOT INTENDED FOR USE IN LIEU OF ENGINEERED SYSTEMS NOT TO BE MULTIPLE MOUNTED IN LARGER THAN SPECIFIED AREAS.



HORIZONTAL

TD I	MOLTIPORPOSE ABC										
VERTICAL	Figure No.	Capacity (lbs.)	Length	Depth	Vertical	Horizontal	Operating Pressure	Coverage Area	Shipping Weight (Ibs)		
	4422V	2	14 1/4	2 7/8	Х		100PSI	4 X 4	4 Lbs.		
	4422H	2	13 7/8	2 7/8		Х	100PSI	4 X 4	4 Lbs.		
	4425V	5	17 1/4	4 1/4	Х		100PSI	4 x 6	11 Lbs.		
	4425H	5	17	4 1/4		Х	100PSI	4 x 6	11 Lbs.		
	4430V	10	20	6	Х		100PSI	10 x 10	19 Lbs.		
	4430H	10	20 5/8	5 11/16		Х	100PSI	10 x 10	19 Lbs.		
	4440V	20	21 7/8	7 1/2	Х		100PSI	12 x 13	36 Lbs.		
	4440H	20	20 15/16	7 1/2		Х	100PSI	12 x 13	36 Lbs.		
-											

MILL TIDLIDDOGE ADC

HALOTRON

Capacity	Length						
	Length	Depth	Vertical	Horizontal	Operating	Coverage	Weight
(lbs.)					Pressure	Area	(lbs.)
18	17 7/8	7	Х		100PSI	4 X 4	29 Lbs.
18	16 13/16	7		Х	100PSI	4 X 4	30 Lbs.
25	21 7/8	7 1/2	Х		100PSI	6 x 6	42 Lbs.
25	20 13/16	7 1/2		Х	100PSI	6 X 6	41 Lbs.
	18 18 25	18 17 7/8 18 16 13/16 25 21 7/8	18 17 7/8 7 18 16 13/16 7 25 21 7/8 7 1/2	18 17 7/8 7 X 18 16 13/16 7 25 21 7/8 7 1/2 X	18 17 7/8 7 X 18 16 13/16 7 X 25 21 7/8 7 1/2 X	18 17 7/8 7 X 100PSI 18 16 13/16 7 X 100PSI 25 21 7/8 7 1/2 X 100PSI	18 17 7/8 7 X 100PSI 4 X 4 18 16 13/16 7 X 100PSI 4 X 4 25 21 7/8 7 1/2 X 100PSI 6 x 6