

SINGLE JACKET ALL SYNTHETIC POLYURETHANE LINED 500LB. TEST - RACK HOSE

Approved - 500 lb. Test. (Service Test Pressure 250 lbs.)

Industry standard lightweight hose for pin racks. Totally immune to mildew

STANDARD EQUIPMENT: Single Jacket Polyurethane lined, 100% Synthetic Jacket. FM

OPTIONAL: U/L Label. (Note: When U/L is used with this hose it is marked 300 lb. Test, per U/L 19.)



3401-3402 Series
 Figure
 Lengths

 No.
 Size
 Available


 3401
 1 1/2
 50'

 3402
 2 1/2
 75'-100'

and rot.



SINGLE JACKET EPDM LINED 300 LB. TEST - RACK HOSE



3405-3406 Series A lightweight hose, ideal for use with hose rack units. All polyester jacket. Totally immune to mildew and rot. Lined hose reduces friction loss and eliminates water seepage. **STANDARD EQUIPMENT**: Single Jacket EPDM Lined, All Polyester Jacket. All FM Approved - 300lb. Test. (Service Test Pressure 150 lbs.) **OPTIONAL**: U/L Label

A lightweight hose, ideal for interior rack use and exterior use as well. Totally immune to

mildew and rot. Use on racks and reels where longer service life is required. **STANDARD EQUIPMENT**: Single Jacket EPDM Lined, All Polyester hose. All FM

Figure No.	Size	Lengths Available
3405	1 1/2	50'
3406	2 1/2	75'-100'



SINGLE JACKET EPDM LINED 500 LB. TEST - RACK HOSE

Approved - 500lb. Test. (Service Test Pressure 250 lbs.)

OPTIONAL: U/L Label - Color impregnation.



3410-3411 Series

Figure No.	Size	Lengths Available
3410	1 1/2	50'
3411	2 1/2	75'-100'



SINGLE JACKET EPDM LINED 300 LB. TEST



3415-3416 Series Ideal for industrial applications where hose is stored for prolonged periods. Particularly suitable for use with reels and exterior hose houses. Totally immune to mildew and rot. NOT for rack installation.

STANDARD EQUIPMENT: Single Jacket EPDM Lined, All Polyester hose. All FM Approved - 300lb. Test. (Service Test Pressure 150 lbs.) OPTIONAL: U/L Label - Color impregnation.

Figure No.	Size	Lengths Available
3415	1 1/2	50'
3416	2 1/2	75'-100'

