

**SINGLE WATERWAY MONITOR**

**Figure No. 9004**



Fixed installation for one man operation where high gallonages are required. Intended for permanent, stationary protection of high risk areas.

**STANDARD EQUIPMENT:** Red painted brass body. Positive locking control. Pressure gun grease fitting. Full 360 degree horizontal traverse.

**NOZZLE NOT INCLUDED. SEE PAGE 9-6.**

**Figure No. 9004**

Fig. No.	Operated	Material	G.P.M.	Outlet	Base Options
9004	Worm Gear	Brass	1250	2 1/2"	3" NPT Female 3" or 4" Flange

**HANDLE OPERATED MONITORS**

**Factory Mutual Approved**

**Figure No. 9006**



**Figure No. 9006**

Fixed installation for one man operation where high gallonages are required. Intended for permanent, stationary protection of high risk areas.

**STANDARD EQUIPMENT:** All brass construction with stainless steel and brass twist locking mechanism. Stainless steel handle rod. Grease fittings on lower swivels. Red enamel finish. Full 360 degree horizontal traverse. **NOZZLE NOT INCLUDED. SEE PAGE 9-6.**

Fig. No.	Operated	Material	G.P.M.	Outlet	Base Options
9006	Handle	Brass	750	2 1/2"	2 1/2", 3" 4" Female NPT Flange 125-150ASA 2 1/2", 3", 4", 6" Flange 250-300ASA 2 1/2", 3", 4"