

HYFLO

FIRE PROTECTION

HYF-555-OS Cast Iron Body Gate Valve Outside Screw and Yoke Face to Face

Application: Fire Protection/Air-condition/Plumping

Meet UL 262/FM 1120 SPEC

Face to Face to ANSI B16.10 flanged ends to ANSI B16.1 CL125

175psi/12.1 BAR Working Pressure For Non Shock Cold Water

UL listed – FM approved

Test pressure 350PSI Water

MATERIAL SPECIFICATIONS

No	Part	QTY
1	Seat Ring	2
2	Disc Ring	2
3	Disc	1
4	Body	1
5	Gasket	1
6	Bonnet	1
7	Bolt Nut	4" 12
8	Stem	1
9	Yoke Sleeve Nut	1
10	Packing	1
11	Gland Flange	1
12	Yoke	2
13	Gland Bolt	2
14	Gland Nut	2
15	Bonnet&Yoke Bolt&Nut	4
16	Stem Nut	1
17	Retaining Nut	1
18	Hand Wheel	1
19	Yoke Bolt & Nut	2

DIMENSION

Size	L (mm)	T (mm)	D (mm)	H (mm)	W (mm)	WT LBS
2"	177.8	19.1	152.4	327	152.4	44.0
2-1/2"	190.5	19.1	177.8	368	152.4	56.0
3"	203.2	19.1	190.5	400	203.2	74.0
4"	228.6	23.8	228.6	495	254	115.0
5"	254	23.8	254	580	305	159.0
6"	266.7	25.4	279.4	640	305	194.0
8"	292.1	28.6	342.9	819	355	308.0
10"	330.2	30.2	406.4	980	281	495.0
12"	355.5	31.8	482.6	1127	406	693.0

HYF-555-OS

