

HYFLO

FIRE PROTECTION

HYF - A Fire Angle Hose Valve – 300PSI

Application: Fire Protection
 Brass Valve Red Hand Wheel
 Female NPT Inlet & Female Thread Outlet
 UL listed – FM approved

MATERIAL SPECIFICATIONS

No.	PART	SPECIFICATION
1	Body	Brass B584 C854 C85700
2	Bonnet	Brass B584 C854 C85700
3	Holder	Brass B584 C854 C85700
4	Stem	Brass ROD B16
5	Hand Wheel	Ductile Iron
6	O - Ring	NBR
7	Packing Nut	Brass ROD B16
8	Seat Seal	NBR
9	Lock Nut	Brass ROD B16
10	Clamping Ring	Brass ROD B16
11	Clamping Nut	Brass ROD B16
12	Wheel Washer	Mild Steel
13	Wheel Nut	Mild Steel
14	Set Screw	Brass ROD B16

DIMENSION

Size	A (mm)	B (mm)	C (mm)	E (mm)
1 1/2" X 1 1/2"	3.99" (101.5)		2.44" (62)	
2 1/2" X 2 1/2"	4.92" (125)	5.9" (150)	3.34" (85)	7.67" (195)

Finish
 RB: Rough Brass
 PB: Polished Brass
 RC: Rough Chrome Plated
 PC: Polished Chrome Plated
 RP: Red Painted



HYF-A

